Welcome to STN International! Enter x:x

LOGINID:ssspta1304rxk

PASSWORD:

TERMINAL (ENTER 1, 2, 3, OR ?):2



```
Welcome to STN International
                 Web Page URLs for STN Seminar Schedule - N. America
NEWS
      1
                 "Ask CAS" for self-help around the clock
NEWS 2
                 PATDPAFULL - New display fields provide for legal status
NEWS 3 FEB 28
                 data from INPADOC
NEWS 4 FEB 28 BABS - Current-awareness alerts (SDIs) available
NEWS 5 MAR 02 GBFULL: New full-text patent database on STN
NEWS 6 MAR 03 REGISTRY/ZREGISTRY - Sequence annotations enhanced
NEWS 7 MAR 03 MEDLINE file segment of TOXCENTER reloaded
NEWS 8 MAR 22 KOREAPAT now updated monthly; patent information enhanced
      9 MAR 22 Original IDE display format returns to REGISTRY/ZREGISTRY
NEWS
      10 MAR 22 PATDPASPC - New patent database available
NEWS
      11 MAR 22 REGISTRY/ZREGISTRY enhanced with experimental property tags
NEWS
      12 APR 04 EPFULL enhanced with additional patent information and new
NEWS
                 fields
      13 APR 04
                 EMBASE - Database reloaded and enhanced
NEWS
NEWS
      14 APR 18
                 New CAS Information Use Policies available online
                 Patent searching, including current-awareness alerts (SDIs),
NEWS 15 APR 25
                 based on application date in CA/Caplus and USPATFULL/USPAT2
                 may be affected by a change in filing date for U.S.
                 applications.
                 Improved searching of U.S. Patent Classifications for
NEWS
      16 APR 28
                 U.S. patent records in CA/CAplus
      17 MAY 23
                 GBFULL enhanced with patent drawing images
NEWS
NEWS 18 MAY 23 REGISTRY has been enhanced with source information from
                 CHEMCATS
      19 JUN 06 STN Patent Forums to be held in June 2005
NEWS
NEWS 20 JUN 06 The Analysis Edition of STN Express with Discover!
                  (Version 8.0 for Windows) now available
                 RUSSIAPAT: New full-text patent database on STN
      21 JUN 13
NEWS
                 FRFULL enhanced with patent drawing images
NEWS
      22 JUN 13
NEWS 23 JUN 20
                 MEDICONF to be removed from STN
NEWS EXPRESS JUNE 13 CURRENT WINDOWS VERSION IS V8.0, CURRENT
              MACINTOSH VERSION IS V6.0c(ENG) AND V6.0Jc(JP),
              AND CURRENT DISCOVER FILE IS DATED 13 JUNE 2005
NEWS HOURS
              STN Operating Hours Plus Help Desk Availability
              General Internet Information
NEWS INTER
              Welcome Banner and News Items
NEWS LOGIN
              Direct Dial and Telecommunication Network Access to STN
NEWS PHONE
              CAS World Wide Web Site (general information)
Enter NEWS followed by the item number or name to see news on that
```

Enter NEWS followed by the item number or name to see news on that specific topic.

All use of STN is subject to the provisions of the STN Customer agreement. Please note that this agreement limits use to scientific research. Use for software development or design or implementation of commercial gateways or other similar uses is prohibited and may result in loss of user privileges and other penalties.

```
=> file registry
COST IN U.S. DOLLARS
FULL ESTIMATED COST
```

SINCE FILE TOTAL ENTRY SESSION 0.21 0.21

FILE 'REGISTRY' ENTERED AT 16:36:05 ON 24 JUN 2005 USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT. PLEASE SEE "HELP USAGETERMS" FOR DETAILS. COPYRIGHT (C) 2005 American Chemical Society (ACS)

Property values tagged with IC are from the ZIC/VINITI data file provided by InfoChem.

STRUCTURE FILE UPDATES: 23 JUN 2005 HIGHEST RN 852898-09-0 DICTIONARY FILE UPDATES: 23 JUN 2005 HIGHEST RN 852898-09-0

New CAS Information Use Policies, enter HELP USAGETERMS for details.

TSCA INFORMATION NOW CURRENT THROUGH JANUARY 18, 2005

Please note that search-term pricing does apply when conducting SmartSELECT searches.

Crossover limits have been increased. See HELP CROSSOVER for details.

Experimental and calculated property data are now available. For more information enter HELP PROP at an arrow prompt in the file or refer to the file summary sheet on the web at: http://www.cas.org/ONLINE/DBSS/registryss.html

```
=> s (ni 0-62)/mac
        293159 NI/MAC
        781887 0-62/MAC
        257206 (NI 0-62)/MAC
L1
                 (NI/MAC (P) 0-62/MAC)
=> s 1 and (co 15-25)/mac
      17434332 1
        118083 CO/MAC
        233472 15-25/MAC
         15591 (CO 15-25)/MAC
                 (CO/MAC (P) 15-25/MAC)
          6917 1 AND (CO 15-25)/MAC
L2
=> s 2 and (cr 15-25)/mac
      18760891 2
        297766 CR/MAC
        233472 15-25/MAC
         84992 (CR 15-25)/MAC
                 (CR/MAC (P) 15-25/MAC)
         49062 2 AND (CR 15-25)/MAC
L3
=> s 3 and (co 15-25)/mac
      14838039 3
        118083 CO/MAC
        233472 15-25/MAC
         15591 (CO 15-25)/MAC
```

(CO/MAC (P) 15-25/MAC)

5003 3 AND (CO 15-25)/MAC

L4

BBK. 6-24-05

```
=> s.14 and (al 5-15)/mac
        226113 AL/MAC
        381692 5-15/MAC
         38189 (AL 5-15)/MAC
                 (AL/MAC (P) 5-15/MAC)
           559 L4 AND (AL 5-15)/MAC
L5
=> s 15 and (Y 0.1-1.0)/mac
         12138 Y/MAC
        525383 0.1-1.0/MAC
          5956 (Y 0.1-1.0)/MAC
                 (Y/MAC (P) 0.1-1.0/MAC)
            96 L5 AND (Y 0.1-1.0)/MAC
L6
=> s 16 and (pt 0-35)/mac
        14905 PT/MAC
        772091 0-35/MAC
          7364 (PT 0-35)/MAC
                 (PT/MAC (P) 0-35/MAC)
             3 L6 AND (PT 0-35)/MAC
L7
=> s 17 and (hf 0-5)/mac
         12957 HF/MAC
        666003 0-5/MAC
          8532 (HF 0-5)/MAC
                 (HF/MAC (P) 0-5/MAC)
L8
             0 L7 AND (HF 0-5)/MAC
=> d 17 1-3 all
    ANSWER 1 OF 3 REGISTRY COPYRIGHT 2005 ACS on STN
L7
     165102-77-2 REGISTRY
RN
ED
     Entered STN: 20 Jul 1995
     Cobalt alloy, base, Co 23-80, Cr 10-50, Al 4-12, Ta 3-8, Pt 3-6, Y 0.1-1
CN
     (9CI) (CA INDEX NAME)
MF
    Al . Co . Cr . Pt . Ta . Y
CI
    AYS
SR
     CA
LC
     STN Files:
                 CA, CAPLUS, USPATFULL
DT.CA Caplus document type: Patent
     Roles from patents: USES (Uses)
Component
           Component
                          Component
                       Registry Number
            Percent
Co
          23
              - 80
                           7440-48-4
   Cr
          10
                  50
                           7440-47-3
                           7429-90-5
                  12
   Al
           4
   Ta
           3
                   8
                           7440-25-7
                   6
    Pt
                           7440-06-4
           3
    Υ
           0.1 -
                   1
                           7440-65-5
               1 REFERENCES IN FILE CA (1907 TO DATE)
               1 REFERENCES IN FILE CAPLUS (1907 TO DATE)
REFERENCE 1
AN
    123:63362 CA
```

TI Alloys and dispersion composites for coating resistant to hot corrosion and oxidation in gas-turbine service

IN Bettridge, David Frederick; Taylor, Thomas Alan; Tucker, Robert Clark, Jr.

PA Rolls-Royce PLC, UK; Praxair Inc.

SO Eur. Pat. Appl., 19 pp. CODEN: EPXXDW

DT Patent

LA English

IC ICM C23C004-06

RRK. G-24-05

```
ICS C23C030-00; C23C004-18
     56-3 (Nonferrous Metals and Alloys)
     Section cross-reference(s): 57
FAN.CNT 1
                                          APPLICATION NO.
                                                            DATE
     PATENT NO.
                     KIND DATE
                     _ _ _ _
                                           EP 1994-308035
                                                            19941101
                            19950510
PΙ
     EP 652299
                      A1
     EP 652299
                      В1
                            19961227
     R. AT, CH, DE, FR, GB, IT, LI, SE
                                           US 1993-148460
     US 5455119
                      Α
                            19951003
                                                            19931108
                      E
                                           AT 1994-308035
                                                            19941101
     AT 146825
                            19970115
     CA 2135233
                     AA
                                                            19941107
                            19950509
                                           CA 1994-2135233
                          . 19980714
                     C
     CA 2135233
                                           BR 1994-4361
                                                            19941107
                     Α
                           19950704
     BR 9404361
                                           CN 1994-118165
                                                            19941107
                      Α
                           19950719
    CN 1105396
                      В
                           20000816
     CN 1055512
                    A2 19951003
                                           JP 1994-295973
                                                            19941107
     JP 07252674
                      B2
     JP 2920076
                           19990719
     KR 227237
                      В1
                           19991101
                                           KR 1994-29047
                                                            19941107
PRAI US 1993-148460
                    19931108
     The MCrAlY-type alloys suitable for spray coating (as well as for
AB
     composites with oxide dispersion) contain M (as Fe, Co, and/or Ni)
     nominally at 19-83, Cr 10-50, Al 4-14, Y (and optionally Hf) 0.1-3, and
     optionally addnl. Ta, Re, and/or Pt at 3-14 weight%. The alloys are
     preferably used as composite with an oxide dispersion (especially Al2O3) at 5-20
     volume%, and are suitable for coating of superalloy parts operating in
     high-temperature oxidizing environments. The alloy or composite layer is
     optionally coated with a top layer of ZrO2 or Al and/or Cr, and is
     suitable for thermal barrier service. The typical alloy for powder-spray
     coating 6 mils thick on Mar-M-002 superalloy for gas turbine service
     contains Co 32, Ni 32, Cr 21, Al 8, Y 0.5, and Pt 6 weight%.
     cobalt chromium aluminum yttrium alloy coating; nickel chromium aluminum
ST
     alloy coating; turbine coating chromium aluminum alloy; oxide composite
     chromium alloy coating; thermal barrier chromium alloy composite
IT
     Turbines
        (coatings for; alloy composites with oxide dispersion for coating
        resistant to hot corrosion and oxidation in gas-turbine service)
IT
     Aluminizing
     Chromizing
        (coatings with; alloy composites with oxide dispersion for coating
        resistant to hot corrosion and oxidation in gas-turbine service)
IT
     Coating materials
        (composites; alloy composites with oxide dispersion for coating
       resistant to hot corrosion and oxidation in gas-turbine service)
IT
     Alloys, uses
     RL: TEM (Technical or engineered material use); USES (Uses)
        (thermal barriers on; alloy composites with oxide dispersion for
        coating as thermal barrier on superalloy parts in gas-turbine service)
     7429-90-5, Aluminum, uses 7439-89-6, Iron, uses 7440-02-0, Nickel,
ΙT
                                      7440-15-5, Rhenium, uses
                                                                  7440-25-7,
           7440-06-4, Platinum, uses
                                                  7440-48-4, Cobalt, uses
     Tantalum, uses
                     7440-47-3, Chromium, uses
                               7440-65-5, Yttrium, uses
     7440-58-6, Hafnium, uses
     RL: MOA (Modifier or additive use); USES (Uses)
        (alloys containing; alloys and dispersion composites for coating resistant
        to hot corrosion and oxidation in gas-turbine service)
IT
     61048-41-7
                  61048-42-8
     RL: MOA (Modifier or additive use); USES (Uses)
        (coatings; alloy composites with oxide dispersion for coatings
        resistant to hot corrosion and oxidation in gas-turbine service)
                                               165047-06-3
ΙT
     165047-03-0
                   165047-04-1
                                 165047-05-2
                                                             165047-07-4
                   165047-09-6
                                 165047-10-9
                                               165047-11-0
                                                             165047-12-1
     165047-08-5
                                 165047-15-4
                                               165047-16-5
                                                             165102-69-2
     165047-13-2
                   165047-14-3
     165102-70-5
                   165102-71-6
                                 165102-72-7
                                               165102-73-8
                                                             165102-74-9
     165102-75-0
                   165102-76-1
                                 165102-77-2
     RL: TEM (Technical or engineered material use); USES (Uses)
        (coatings; alloy composites with oxide dispersion for coatings
        resistant to hot corrosion and oxidation in gas-turbine service)
ΙT
     1314-20-1, Thoria, uses 1314-23-4, Zirconia, uses 1314-36-9, Yttria,
```

```
12055-23-1, Hafnia
uses
       1344-28-1, Alumina, uses
RL: MOA (Modifier or additive use); USES (Uses)
   (dispersed; alloy composites with oxide dispersion for coatings
   resistant to hot corrosion and oxidation in gas-turbine service)
ANSWER 2 OF 3 REGISTRY COPYRIGHT 2005 ACS on STN
165102-76-1 REGISTRY
Entered STN: 20 Jul 1995
Nickel alloy, base, Ni 6-62,Co 10-40,Cr 15-25,Al 7-14,Ta 3-8,Pt 3-6,Y
0.1-1 (9CI) (CA INDEX NAME)
Al . Co . Cr . Ni . Pt . Ta . Y
AYS
CA
             CA, CAPLUS, USPATFULL
STN Files:
```

Component	Comp Per	cce	nt	Component Registry Number
======+	=====	===	====	:=+==========
Ni	6	-	62	7440-02-0
Co	10	-	40	7440-48-4
Cr	15	-	25	7440-47-3
A1	7	_	14	7429-90-5
Ta	3	-	8	7440-25-7
Pt	3	-	6	7440-06-4
Y	0.1	_	1	7440-65-5

DT.CA CAplus document type: Patent

Roles from patents: USES (Uses)

- 1 REFERENCES IN FILE CA (1907 TO DATE)
- 1 REFERENCES IN FILE CAPLUS (1907 TO DATE)

REFERENCE 1

L7

RN ED

CN

MF

CI

SR

LC

```
AN 123:63362 CA
```

- TI Alloys and dispersion composites for coating resistant to hot corrosion and oxidation in gas-turbine service
- IN Bettridge, David Frederick; Taylor, Thomas Alan; Tucker, Robert Clark, Jr.
- PA Rolls-Royce PLC, UK; Praxair Inc.
- SO Eur. Pat. Appl., 19 pp.

CODEN: EPXXDW

- DT Patent
- LA English
- IC ICM C23C004-06
 - ICS C23C030-00; C23C004-18
- CC 56-3 (Nonferrous Metals and Alloys)
 Section cross-reference(s): 57

FAN.CNT 1

11111.		_												
	PA?	CENT :	NO.		KII	ND.	DATE			API	PLICATION	NO.	DATE	
ΡI	ΕP	6522	99	•	A.	l	1995	0510		EP	1994-308	035	199411	01
	ΕP	6522	99		B.	l	1996	1227		•				
		R:	ΑT,	CH,	DE,	FR	GB,	IT,	LI,	SE				
	US	5455	119		Α		1995	1003		US	1993-148	460	199311	80
	AT	1468	25		E		1997	0115		AT	1994-308	035	199411	01
	CA	2135	233		A.	A	1995	0509		CA	1994-213	5233	199411	07
	CA	2135	233		С		1998	0714						
	BR	9404	361		Α		1995	0704		BR	1994-436	1	199411	07
	CN	1105	396		Α		1995	0719		CN	1994-118	165	199411	07
	CN	1055	512		В		2000	0816						
	JP	0725	2674		A2	2	1995	1003		JP	1994-295	973	199411	07
	JP	2920	076		B2	2	1999	0719						
	KR	2272	37		В:	L	1999	1101		KR	1994-290	47	199411	07
		1000	1 40	^	100									

PRAI US 1993-148460 19931108

AB The MCrAlY-type alloys suitable for spray coating (as well as for composites with oxide dispersion) contain M (as Fe, Co, and/or Ni) nominally at 19-83, Cr 10-50, Al 4-14, Y (and optionally Hf) 0.1-3, and optionally addnl. Ta, Re, and/or Pt at 3-14 weight%. The alloys are preferably used as composite with an oxide dispersion (especially Al2O3) at 5-20

000 K. 6-24-05

volume%, and are suitable for coating of superalloy parts operating in high-temperature oxidizing environments. The alloy or composite layer is optionally coated with a top layer of ZrO2 or Al and/or Cr, and is suitable for thermal barrier service. The typical alloy for powder-spray coating 6 mils thick on Mar-M-002 superalloy for gas turbine service contains Co 32, Ni 32, Cr 21, Al 8, Y 0.5, and Pt 6 weight%. cobalt chromium aluminum yttrium alloy coating; nickel chromium aluminum ST alloy coating; turbine coating chromium aluminum alloy; oxide composite chromium alloy coating; thermal barrier chromium alloy composite IT Turbines (coatings for; alloy composites with oxide dispersion for coating resistant to hot corrosion and oxidation in gas-turbine service) ΙT Aluminizing Chromizing (coatings with; alloy composites with oxide dispersion for coating resistant to hot corrosion and oxidation in gas-turbine service) IT Coating materials (composites; alloy composites with oxide dispersion for coating resistant to hot corrosion and oxidation in gas-turbine service) ΙT Alloys, uses RL: TEM (Technical or engineered material use); USES (Uses) (thermal barriers on; alloy composites with oxide dispersion for coating as thermal barrier on superalloy parts in gas-turbine service) 7439-89-6, Iron, uses 7440-02-0, Nickel, ΙT 7429-90-5, Aluminum, uses 7440-15-5, Rhenium, uses 7440-06-4, Platinum, uses Tantalum, uses 7440-47-3, Chromium, uses 7440-48-4, Cobalt, uses 7440-58-6, Hafnium, uses 7440-65-5, Yttrium, uses RL: MOA (Modifier or additive use); USES (Uses) (alloys containing; alloys and dispersion composites for coating resistant to hot corrosion and oxidation in gas-turbine service) ΙT 61048-41-7 61048-42-8 RL: MOA (Modifier or additive use); USES (Uses) (coatings; alloy composites with oxide dispersion for coatings resistant to hot corrosion and oxidation in gas-turbine service) 165047-07-4 165047-05-2 165047-06-3 IT 165047-03-0 165047-04-1 165047-08-5 165047-09-6 165047-10-9 165047-11-0 165047-12-1 165047-13-2 165047-14-3 165047-15-4 165047-16-5 165102-69-2 165102-70-5 165102-73-8 165102-74-9 165102-71**-**6 165102-72-7 165102-76-1 165102-77-2 165102-75-0 RL: TEM (Technical or engineered material use); USES (Uses) (coatings; alloy composites with oxide dispersion for coatings resistant to hot corrosion and oxidation in gas-turbine service) 1314-20-1, Thoria, uses 1314-23-4, Zirconia, uses 1314-36-9, Yttria, 1344-28-1, Alumina, uses 12055-23-1, Hafnia RL: MOA (Modifier or additive use); USES (Uses) (dispersed; alloy composites with oxide dispersion for coatings resistant to hot corrosion and oxidation in gas-turbine service) ANSWER 3 OF 3 REGISTRY COPYRIGHT 2005 ACS on STN RN165102-70-5 REGISTRY EDEntered STN: 20 Jul 1995 Nickel alloy, base, Ni 14-65, Co 10-40, Cr 15-25, Al 7-14, Pt 3-6, Y 0.1-1 (9CI) (CA INDEX NAME) Al . Co . Cr . Ni . Pt . Y AYS CI SR CA CA, CAPLUS, USPATFULL LCSTN Files: DT.CA CAplus document type: Patent RL.P Roles from patents: USES (Uses) r


Component	Component			Component			
	· P6	erce	nt	Registry	Number		
======+	====	====	====	=+======			
Ni	14	-	65	7440-	02-0		
Co	10	-	40	7440-	48-4		
Cr	15	-	25	7440-	47-3		
Al	7	-	14	7429-	90-5		
Pt	3	-	6	7440-	06-4		

ΙT

L7

CN

MF



- 1 REFERENCES IN FILE CA (1907 TO DATE)
- 1 REFERENCES IN FILE CAPLUS (1907 TO DATE)

REFERENCE 1

·Y

AN 123:63362 CA

TI Alloys and dispersion composites for coating resistant to hot corrosion and oxidation in gas-turbine service

IN Bettridge, David Frederick; Taylor, Thomas Alan; Tucker, Robert Clark, Jr.

PA Rolls-Royce PLC, UK; Praxair Inc.

SO Eur. Pat. Appl., 19 pp.

CODEN: EPXXDW

DT Patent

LA English

IC ICM C23C004-06

ICS C23C030-00; C23C004-18

CC 56-3 (Nonferrous Metals and Alloys)

Section cross-reference(s): 57

FAN.	CNT 1				
	PATENT NO.	KIND	DATE	APPLICATION NO	. DATE
ΡI	EP 652299	.A1	19950510	EP 1994-308035	19941101
	EP 652299	B1	19961227		
	R: AT, CH	DE, FR	, GB, IT, LI,	SE	
	US 5455119	A	19951003	US 1993-148460	19931108
	AT 146825	E	19970115	AT 1994-308035	19941101
	CA 2135233	AA	19950509	CA 1994-213523	3 19941107
	CA 2135233	С	19980714		
	BR 9404361	Α	19950704	BR 1994-4361	19941107
	CN 1105396	Α	19950719	CN 1994-118165	19941107
	CN 1055512	В	20000816		
	JP 07252674	A2	19951003	JP 1994-295973	19941107
	JP 2920076	B2	19990719		
	KR 227237	B1	19991101	KR 1994-29047	19941107
_					

PRAI US 1993-148460 19931108

The MCrAlY-type alloys suitable for spray coating (as well as for composites with oxide dispersion) contain M (as Fe, Co, and/or Ni) nominally at 19-83, Cr 10-50, Al 4-14, Y (and optionally Hf) 0.1-3, and optionally addnl. Ta, Re, and/or Pt at 3-14 weight%. The alloys are preferably used as composite with an oxide dispersion (especially Al2O3) at 5-20 volume%, and are suitable for coating of superalloy parts operating in high-temperature oxidizing environments. The alloy or composite layer is optionally coated with a top layer of ZrO2 or Al and/or Cr, and is suitable for thermal barrier service. The typical alloy for powder-spray coating 6 mils thick on Mar-M-002 superalloy for gas turbine service contains Co 32, Ni 32, Cr 21, Al 8, Y 0.5, and Pt 6 weight%.

ST cobalt chromium aluminum yttrium alloy coating; nickel chromium aluminum alloy coating; turbine coating chromium aluminum alloy; oxide composite chromium alloy coating; thermal barrier chromium alloy composite

IT Turbines

(coatings for; alloy composites with oxide dispersion for coating resistant to hot corrosion and oxidation in gas-turbine service)

IT Aluminizing

Chromizing

(coatings with; alloy composites with oxide dispersion for coating resistant to hot corrosion and oxidation in gas-turbine service)

IT Coating materials

(composites; alloy composites with oxide dispersion for coating resistant to hot corrosion and oxidation in gas-turbine service)

IT Alloys, uses

RL: TEM (Technical or engineered material use); USES (Uses) (thermal barriers on; alloy composites with oxide dispersion for coating as thermal barrier on superalloy parts in gas-turbine service)


IT 7429-90-5, Aluminum, uses 7439-89-6, Iron, uses 7440-02-0, Nickel, uses 7440-06-4, Platinum, uses 7440-15-5, Rhenium, uses 7440-25-7, Tantalum, uses 7440-47-3, Chromium, uses 7440-48-4, Cobalt, uses




3 7440-58-6, Hafnium, uses 7440-65-5, Yttrium, uses RL: MOA (Modifier or additive use); USES (Uses) (alloys containing; alloys and dispersion composites for coating resistant to hot corrosion and oxidation in gas-turbine service) 61048-41-7 61048-42-8 IT RL: MOA (Modifier or additive use); USES (Uses) (coatings; alloy composites with oxide dispersion for coatings resistant to hot corrosion and oxidation in gas-turbine service) 165047-06-3 165047-03-0 165047-04-1 165047-05-2 165047-07-4 IT 165047-11-0 165047-08-5 165047-09-6 165047-10-9 165047-12-1 165047-14-3 165047-15-4 165047-16-5 165102-69-2 165047-13-2 165102-72-7 165102-73-8 165102-74-9 165102-70-5 165102-71-6 165102-76-1 165102-77-2 165102-75-0 RL: TEM (Technical or engineered material use); USES (Uses) (coatings; alloy composites with oxide dispersion for coatings resistant to hot corrosion and oxidation in gas-turbine service) 1314-36-9, Yttria, 1314-20-1, Thoria, uses 1314-23-4, Zirconia, uses IT 1344-28-1, Alumina, uses 12055-23-1, Hafnia RL: MOA (Modifier or additive use); USES (Uses) (dispersed; alloy composites with oxide dispersion for coatings resistant to hot corrosion and oxidation in gas-turbine service)

CONFOS

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
15	28	(("20020068008") or ("4675204") or ("4808055") or ("4937042") or ("5076897") or ("5374319") or ("5395584") or ("5554837") or ("5622638") or ("5701669") or ("5997248") or ("6149389") or ("6221175") or ("6410159")):PN.	US-PGPUB; USPAT; USOCR; EPO; JPO;			2005/06/24 12:00





Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
6.	28	(("20020068008") or ("4675204") or ("4808055") or ("4937042") or ("5076897") or ("5374319") or ("5395584") or ("5554837") or ("5622638") or ("5701669") or ("5997248") or ("6149389") or ("6221175") or ("6410159")).PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:02
L2	1859	(420/437 or 420/440 or 420/444 or 420/445 or 420/456 or 420/460 or 420/588 or 148/425 or 148/428).ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:05
13	175	2 and (nickel or ni) and cobalt and (aluminum or aluminium or al) and yttrium and (chromium or cr) and (platinum or pt or hafnium or hf or silicon or si or zirconium or zr or tantalum or ta or rhenium or re or ruthenium or ru)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:07
L4	95	3 and turbine SAME (blade or blades)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:08
L5	77	4 and (coating or coatings or layer or layers)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:09
L6	6	5 and platinum and hafnium and silicon and zirconium and tantalum and rhenium and ruthenium	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:19
L7	11	4 and blade WITH tip	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:32
L8	5535	(428/678 or 428/636 or 428/637 or 428/926 or 428/934 or 427/596 or 427/597 or 427/405 or 416/241).ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:34



L9	793	8 and (platinum or pt)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:35
L10	0	9 and (nickel or ni) and cobalt and (chromium or cr) and (aluminum or aluminium or al) and (silicon or si) and yttrium and (hafnium or hf or zirconium or zr or tantalum or ta or rhenium or re or ruthenium or ru).ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:38
L11	0	8 and 10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:38
L12	106	9 and mcraly	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:39
L13	62	12 and (nickel or ni) and cobalt and yttrium and (aluminum or aluminium or al) and (chromium or cr)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:39
L14	1	13 and blade WITH tip	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 12:46

ROOK	?
Q-28	4-05

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
LI		("5455119").PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/06/24 16:45